

# MIRO

## CRACK FILLER PASTE



**MIRO Crack Filler Paste** is a ready-to-use, flexible, fiber-reinforced acrylic emulsion polymer-based putty. Specially formulated for filling cracks on both internal and external plastered surfaces, offering excellent bonding, ease of application, and lasting durability

### FEATURES & BENEFITS

- Single-pack, ready-to-use: No mixing required, convenient to apply.
- High adhesion: Bonds strongly with cementitious surfaces; prevents recurrence of cracks.
- Flexible formula: Accommodates minor movements in cracks with of Further cracking.
- Water-resistant: Protects surfaces from moisture and leakage.
- Non-sagging: Holds position easily, even on vertical surfaces.
- Eco-friendly and non-toxic: Safe for indoor use, low VOC emission
- Paintable: Compatible with all types of paints after full cure (typically 3 hours).
- Aesthetic finish: Blends smoothly for a neat, professional look.

### DIRECTIONS FOR USE

- Clean the crack and the surrounding surface to remove dust and loose material.
- Apply Crack Filler Paste directly to the area, pressing firmly and leveling the surface.
- Allow to set for 3 hours before applying an additional coat if required.
- Once fully dry, finish with paint or surface treatment as desired.
- Clean tools and hands with soap and water immediately after use.

### AREAS OF APPLICATION

- Suitable for internal and external wall cracks in plastered brick masonry.
- Ideal for cracks up to 20 mm in width.
- Can be used to repair hairline cracks and prevent moisture ingress.

## TECHNICAL PROPERTIES

| PROPERTY                | VALUE                        |
|-------------------------|------------------------------|
| Form                    | Smooth, thick paste          |
| Colour                  | Milky/Off-white              |
| Density at 30°C         | 1.45 -1.50 g/cm <sup>3</sup> |
| Cracks accommodated     | Up to 5-20mm width           |
| Water resistance        | EXCELLENT                    |
| Extension recovery      | 60%                          |
| Application temperature | 5°C to 42°C                  |
| Shelf life              | Up to 24 months              |

### PACKAGING:

AVAILABLE IN 250GM AND 500GM PACKING

### PRECAUTIONS

- Not suitable for cracks wider than 20 mm or for movement/expansion joints.
- Not intended for structural repairs or use on metal surfaces.

